

NOTES:

- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH \$1 TO <1 arcmin
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: RAVG ≤1.75% @ 400 - 700nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): $\lambda/4 \ (\text{per inch over clear aperture})$





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2		
SHAPE	PLANO	PLANO		
SURFACE QUALITY	60-40	60-40		
WAVELENGTH RANGE	400 - 700nm	400 - 700nm		
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED		
ļ				

			Edmund Optics®			
	THIRD ANGLE PROJECTION		TITLE	25mm DIA., 4mm THICK, MGF2 COATED λ/4 N-BK7 WINDOW		
D	ALL DIMS IN	mm	DWG NO	45258	SHEET 1 OF 1	